

#### Fabritec, LLC. 7531 Coldwater Canyon Avenue | North Hollywood | CA | 91605 tel 800.828.2500 (toll-free) or 818.503.8300 | fax 818.503.8360

### Fabritec Solar Solutions™ □ Rollstar™ Order Form

**p.1** of 3

Fabric Description

A fully completed order form is required before manufacturing can begin. All orders confirmed in writing.

Address  City/Stato/ZIP  Phone Fax Phone Ordered by Purchase Order # Purchase Order # Date Needed  Sidemark Acct Mgr Ship via Will Cell Standard 2-2-Day  In the No Shades (Coty) Is So Will Cell Continue to Will Cell Standard 2-2-Day  Will Cell Standard 2	Account #		A	ccou	ınt N	lame						-	Ship to	Э								A	Attn				
Phone   Fax	Address											2	Addre	ss													
Date Ordered by   Purchase Order #   Date Ordered   Date Ordered   Date Needed	City/State/ZIP												City/S	tate/Z	ΊΡ												
Sidemark  Acct Mgr  Ship via   Will Call   Standard   2-Day    Standard   2-Day	Phone						Fax						Phone	<b>:</b>													
Sidemark  Acct Mgr  Ship via   Will Call   Standard   2-Day    Line No Shades   Mount   WIDTH-   Tight   Tight   Tight   Tight   Width   Gopening   Bradesto   Width   Height   Reg   Rev   Standard   Standard   Standard   Light   HEM OPTION DETA   Line No Standard   Light   HEM OPTION DETA   Light   Hem Dar Ct   Style   Annot Annot   Light   Hem Dar Ct   Style   Light   Light   Hem Dar Ct   Style   Light   Light   Hem Dar Ct   Style   Light   Light   Hem Dar Ct   Style   Light   Light	Ordered by						Purchase	Order #				-	Date C	Ordere	ed								Date	Needec			
Line No & Shades (City) Is Os Wall Call Opening Bracket to United Paracket To United Para								Acct	Mar			-	Ship v	ia		□ w	/ill C	all		□s	Stand	dard			2-Da	av	
Line No & Shades Room ID    Tight   Ti												-															
Line No Room ID  Room ID  Room ID  Room ID  Room ID  Line No Room ID  Line No Room ID  Ro			Τ					WIDTH*			Roll				LIFTI	NG S	YSTE	EMS				Lic	ıht	HEM C	PTIO!	N DET	AILS
1. 2. 3. 4. 5. 6. 7. 8. 8. *About WIDTH: Tight Opening is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a ½" allowance for inside mount. For outside mount, this is the actual measurement. Tip to Tip is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket to outside of bracket.  Cloth Width will be ¾" to 1¾" less than the tip to tip width (or bracket to bracket), depending on the application. Please call for specifics.  (A) Chain length cannot be less than ¾ of the height of the shade.  (B) Motor selection and option details must be specified. Please refer to page 2 of this order form.  □ I have ordered MOTOR(s) on page 2 of this order form.  □ I have ordered OPTIONS on pages 2 & 3 of this order form.	&			Mo	ount		Tight		Cloth			ring	/stem	/olite	Sord- + Rail	dless	C	00				Cha			Hen	n Bar (	Color
2. 3. 4. 5. 6. 7. 8. Tight Opening is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a 1/6" allowance for inside mount, this is the actual measurement.  Tip to Tip is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket to outside of bracket.  Cloth Width will be 9/4" to 19/4" less than the tip to tip width (or bracket to bracket), depending on the application. Please call for specifics.  (A) Chain length cannot be less than 3/4 of the height of the shade.  (B) Motor selection and option details must be specified. Please refer to page 2 of this order form.  I have ordered MOTOR(s) on page 2 of this order form.  I have ordered OPTIONS on pages 2 8.3 of this order form.  Round Hem Bar, Shadow II have ordered OPTIONS on pages 2 8.3 of this order form.	Room ID	(4.9)	IS	os	Wal	Ceil		(Bracket to		1 10.g. 10	Reg Rev	S G	SL S	Lou	Std (	Corc	L	R		L	R	Side	Sill	l. *	Anod Black	Anod Alum	White
3. 4. 5. 6. 7. 8. *About WIDTH: Tight Opening is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a '%' allowance for inside mount. For outside mount, this is the actual measurement.  Tight Opening is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket to outside of bracket.  Cloth Width will be '%' to 1%' less than the tip to tip width (or bracket), depending on the application. Please call for specifics.  (A) Chain length cannot be less than % of the height of the shade.  (B) Motor selection and option details must be specified. Please refer to page 2 of this order form.  I have ordered MOTOR(s) on page 2 of this order form.  I have ordered OPTIONS on pages 2 & 3 of this order form.  Round Hem Bar, Shadow I Round Hem Ba	1.																										
*About WIDTH:  Tight Opening is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a %" allowance for inside mount. For outside mount, this is the actual measurement.  Tip to Tip is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket to outside of bracket to usual window measurement.  Cloth Width will be %" to 1%" less than the tip to tip width (or bracket to bracket), depending on the application. Please call for specifics.  (A) Chain length cannot be less than % of the height of the shade.  (B) Motor selection and option details must be specified. Please refer to page 2 of this order form.  I have ordered MOTOR(s) on page 2 of this order form.  I have ordered OPTIONS on pages 2 & 3 of this order form.	2.																										
5. 6. 7. 8.  *About WIDTH:  Tight Opening is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a 1/6" allowance for inside mount, this is the actual measurement.  Tip to Tip is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket to outside of bracket.  Cloth Width will be 3/4" to 11/4" less than the tip to tip width (or bracket to bracket), depending on the application. Please call for specifics.  (A) Chain length cannot be less than 3/4 of the height of the shade.  (B) Motor selection and option details must be specified. Please refer to page 2 of this order form.  I have ordered MOTOR(s) on page 2 of this order form.  I have ordered OPTIONS on pages 2 & 3 of this order form.  Round Hem Bar, Shadou	3.																										
*About WIDTH:  Tight Opening is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a 1/6" allowance for inside mount. For outside mount, this is the actual measurement.  Tip to Tip is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket to outside of bracket.  Cloth Width will be 3/4" to 13/4" less than the tip to tip width (or bracket to bracket), depending on the application. Please call for specifics.  (A) Chain length cannot be less than 3/4 of the height of the shade.  (B) Motor selection and option details must be specified. Please refer to page 2 of this order form.  I have ordered MOTOR(s) on page 2 of this order form.  Bound Hem Bar, Shadou II have ordered OPTIONS on pages 2 & 3 of this order form.	4.																										
*About WIDTH:  Tight Opening is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a 1/4" allowance for inside mount. For outside mount, this is the actual measurement.  Tip to Tip is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket to outside of bracket.  Cloth Width will be 3/" to 13/4" less than the tip to tip width (or bracket to bracket), depending on the application. Please call for specifics.  (A) Chain length cannot be less than 3/4 of the height of the shade.  (B) Motor selection and option details must be specified. Please refer to page 2 of this order form.  I have ordered MOTOR(s) on page 2 of this order form.  Page 2 of this order do OPTIONS on pages 2 & 3 of this order form.  Round Hem Bar, Shadou Leads to the shade from tip to tip or outside of bracket is 3td Pocket (sealed side in the shade from tip to tip or outside of bracket is 3td Pocket (sealed side in the shade from tip to tip or outside of bracket is 3td Pocket (sealed side in the page 2 of Pocket (sealed side in the page 2 of Pocket (sealed side in the shade from tip to tip or outside of bracket is 3td Pocket (sealed side in the page 2 of Pocket (seal	5.																										
*About WIDTH:  Tight Opening is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a ¼" allowance for inside mount. For outside mount, this is the actual measurement.  Tip to Tip is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket to outside of bracket.  Cloth Width will be ¾" to 1¾" less than the tip to tip width (or bracket to bracket), depending on the application. Please call for specifics.  (A) Chain length cannot be less than ¾ of the height of the shade.  (B) Motor selection and option details must be specified. Please refer to page 2 of this order form.  □ I have ordered MOTOR(s) on page 2 of this order form.  □ I have ordered OPTIONS on pages 2 & 3 of this order form.  Round Hem Bar, Shadow II and the material of the shade of the shade from tip to tip or outside of std Pocket (sealed side Non-Std Pocket (sealed side Non-Std Pocket (open so the shade from tip to tip or outside of bracket.  Tip to Tip is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket (sealed side Non-Std Pocket (sealed side Non-Std Pocket (open so the shade from tip to tip or outside of bracket.  Flat Hem Bar, Shadow II flat Hem Bar, Sh	6.																										
*About WIDTH:  Tight Opening is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a 1/6" allowance for inside mount. For outside mount, this is the actual measurement.  Tip to Tip is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket to outside of bracket.  Cloth Width will be 3/4" to 13/4" less than the tip to tip width (or bracket to bracket), depending on the application. Please call for specifics.  (A) Chain length cannot be less than 3/4 of the height of the shade.  (B) Motor selection and option details must be specified. Please refer to page 2 of this order form.  I have ordered MOTOR(s) on page 2 of this order form.  C - HEM STYLES (indicate appropriate code in Std Pocket (sealed side Non-Std Pocket (sealed side Non-Std Pocket (open state)).  The provided is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a 1/6" allowance for inside of bracket.  Std Pocket (sealed side Non-Std Pocket (open state)).  The provided is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a 1/6" allowance for inside of the shade is the actual measurement.  Std Pocket (sealed side Non-Std Pocket (open state)).  Flat Hem Bar, Shadow It	7.																										
Tight Opening is the actual window measurement, usually an inside mount or other tight fitting area. If provided, we will take a 1/6" allowance for inside mount. For outside mount, this is the actual measurement.  Tip to Tip is the same as bracket to bracket. If you provide the tip to tip measurement, this will be the exact size of the shade from tip to tip or outside of bracket to outside of bracket.  Cloth Width will be 3/" to 13/" less than the tip to tip width (or bracket to bracket), depending on the application. Please call for specifics.  (A) Chain length cannot be less than 3/4 of the height of the shade.  (B) Motor selection and option details must be specified. Please refer to page 2 of this order form.  I have ordered MOTOR(s) on page 2 of this order form.  I have ordered OPTIONS on pages 2 & 3 of this order form.  C- HEM STLES (indicate appropriate code in Std Pocket (sealed side Non-Std Pocket (seale	8.																										
Round Hem Bar, Plain  I have ordered MOTOR(s) on page 2 of this order form.  I have ordered OPTIONS on pages 2 & 3 of this order form.  Round Hem Bar, Shado	Tight Opening mount. For outs Tip to Tip is the bracket to outsic Cloth Width wil (A) Chain length	ide mount, the same as brade of bracket. Il be 34" to 13% cannot be le	is is icke 4" le ss tl	the t to k ss th	actu oracl nan t 34 of	ket. I he tip	easurement f you provide to tip width neight of th	t.  de the tip to  th (or bracke  e shade.	tip measul	rement, this	s will be t ling on th	he ex	act siz	ze of t	he sh	ade fr	om t	tip to	tip or o			F	(ind Sto No Fla Fla	d Pocket Drocket Std Pocket Hem B	oropria t (seal ocket 3ar, Pl 3ar, Sh	te code led sid t (oper lain hadow	de her n side v Line
☐ I have ordered MOTOR(s) on page 2 of this order form. ☐ I have ordered OPTIONS on pages 2 & 3 of this order form. ☐ Round Hem Bar, Shado																											
	☐ I have orde	red MOTOR	(s) c	n n	ane	2 of	this order	form	Пі	have orde	red OPT	IONI	Sonr	nanes	228.1	3 of t	his r	orde	r form								
Auditorial Ball, Wildy				-	-																						
	_ mave orde	ISG VALAINO	0	O11 k	Juge			. 101111.		navo givei	. 0. 201	, <u>, ,                                </u>			J. 40 (	,,, U.∏	5 01	GOI				l	110		ואטמו	, vvia	-puu

C - HEM STYLES (indicate appropriate code in above hem style box)	CODE
Std Pocket (sealed side hems)	SP
Non-Std Pocket (open side hems)	NSP
Flat Hem Bar, Plain	FP
Flat Hem Bar, Shadow Line	FSL
Flat Hem Bar, Wrapped	FW
Round Hem Bar, Plain	RP
Round Hem Bar, Shadow Line	RSL
Round Hem Bar, Wrapped	RW

☐ Overnight



# Fabritec, LLC. 7531 Coldwater Canyon Avenue | North Hollywood | CA | 91605 tel 800.828.2500 (toll-free) or 818.503.8300 | fax 818.503.8360

#### Fabritec Solar Solutions™ □ Rollstar™ Order Form

$\square$ I would like help	with MOTOR SEL	<b>ECTION</b> for this	Rollstar order.
-----------------------------	----------------	------------------------	-----------------

			мото	R TYPES / AUTOMATED CO	NTROLS								М	отов	COR	DS*		
For Line No(s)	01		I	POWER SUPPLY		TECHNOLOGY	,	OTI	HER	F	Plug-ir	Cord	S	,	Nithou	ıt Plug	ı	After Market
from page 1	Qty	Vendor	Battery	Low Voltage High Voltage	RTS	Network	DCT	STD Sonesse	UQ Sonesse	3'	6'	12'	24'	3'	3' 6' 12'		24'	Plug

	Leave	motor	limit	settings	in	factory	mode
--	-------	-------	-------	----------	----	---------	------

Qty

For Line No(s) from page 1	SOMFY REMOTE CONTROLLERS Color(s)**	Qty	For Line No(s) from page 1	AUTOMATE REMOTE CONTROLLERS	Qty	For Line No(s) from page 1	AUTOMATE OPTIONS
	1-Ch Hand Held			1-Ch Hand Held			Solar Panel Y-Harness Cable
	5-Ch Hand Held			15-Ch Hand Held			Automate Recharger***
	16-Ch Hand Held			1-Ch Wall Mount			Power Supply Li-ion 1.1 Motor
	1-Ch Wall Mount			2-Ch Wall Mount			Power Supply Li-ion 2.0 Motor
	5-Ch Wall Mount			15-Ch Wall Mount			Sun Sensor
							Pulse Wi-Fi/Arc Bridge Kit (Network)

<sup>\*\*</sup>Colors vary. Refer to page 56 of your Rollstar Price List.

<sup>\*\*\*</sup>At least one is requiired. Can be used on multiple shades.

For Line No(s) from page 1	SOMFY RTS OPTIONS	Qty	For Line No(s) from page 1	SOMFY TRANSFORMER/DISTRIBUTION PANELS (for low voltage applications)	Qty	For Line No(s) from page 1	SOMFY NETWORK CONTROLS	Color(s)**	Qty
	My Llnk			1-Motor Transformer with Plug			SDN Intelligent Switch, 6-Scene		
	Chronis RTS Timer			5-Motor Panel			SDN Intelligent Switch, 8-Scene		
	Sunis RTS (Sun Sensor) Timer			10-Motor Panel			RTS to SDN Interface	N/A	
	Sonesse 30 Wire Free Plug-in Charger***			15-Motor Panel			RTS Repeater	N/A	
	Motor Tester			20-Motor Panel			16-Ch Universal RTS Interface	N/A	
				Power Panel (for SDN)					

<sup>\*\*\*</sup>At least one is requiired. Can be used on multiple shades.

<sup>\*</sup> Standard motor cords are 6 feet without plugs.

<sup>\*\*</sup>Colors vary. Refer to page 56 of your Rollstar Price List.



# Fabritec, LLC. 7531 Coldwater Canyon Avenue | North Hollywood | CA | 91605 tel 800.828.2500 (toll-free) or 818.503.8300 | fax 818.503.8360

### Fabritec Solar Solutions™ □ Rollstar™ Order Form

**p.3** of 3

VALANCE OPTION DETAILS  VALANCE TYPES (Please check appropriate box)  VALANCE COLORS*																											
									V	ALANCE	TYPES (	Please ch	eck appi	opriate b	oox)								VA	LANC	E COL	ORS	)*
For Line No(s) from page 1	Qty	Flat Valance	Covered Cornice	Cassette Plain 31/8" × 21/2"	Cassette Plain 31/8" × 33/8"	Cassette Wrap 31⁄8" × 21⁄2"	Cassette Wrap 31/8" × 33/8"	Cordless Cassette Plain	Cordless Cassette Wrap	Std Cordless with Rail System	SL-System Snap-on Fascia 334" x 336"	SL-System Snap-on Fascia 43%" x 41%"	L-System Fascia 394" x 398"	L-System Fascia 4%" x 41%"	4040 Covered Fascia (top & front) 4" x 4"	5" Snap-on Fascia	7" Snap-on Fascia	4045 Headbox 4" x 4½"	5050 Headbox 4%, x 5"	5555 Headbox 51⁄2" x 51⁄2"	7090 Headbox 9" x 7"	Closure Shelf 27%" x 7%"	Anod. Clear	Anod. Black	Black	White	Bronze

\*Please refer to the colors available for each valance in your Rollstar Price List before filling in your choices in the color boxes above.

	VALANCE OPTION DETAILS (continued)														
For Line No(s)	01	End	Cap	Bottor	n/Closure	e Shelf	Mounting	Intermediate							
from page 1	Qty	L	R	21/2" set	5" set	Custom Color	Brackets (required)	Brackets							

TUBE CONNECTORS														
For Line No(s) from page 1	Qty	Unicoupler	Double Collapsible Coupler-Brkt	Collapsible Coupler-Brkt	Rollease Easy Link Brkt System	Duo Link	Multi Link	Spring Assist for Multi Llnk						

DUC	SHADES	& DUO E	BRACKE	TS		BRACKET COV	ERS, DEC	ORATIVE I	METAL &	STD CC	RDLE	SS WITI	H RAIL	BRACK	(ETS
For Line No(s)	Qty	Universal Slim Brkt	Dble Vert.	Dble Vert. Slim Link	Brkt	For Line No(s)	Brkt Covers for CCOs		Decorat	ive Meta	al Bracke	ets		Std Co with Rail	ordless I System
from page 1	Qty	Slim Brkt	Slim Brkt	Brkt	Covers	from page 1		3%" x 2¼"	3" x 21/4"	Black	White	Chrome	Pewter	Clip Brkt	L-Brkt
															i l

	SPECIAL INSTRUCTIONS
1	